

APPLICANT(S): GAT, Tal et al.
SERIAL NO.: 10/748,173
FILED: December 31, 2003
Page 2

RECEIVED
CENTRAL FAX CENTER
FEB 04 2008

AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows:

1. (Currently Amended) A method comprising:
generating branch predictions for two sequential lines in parallel during a prediction period by:
determining if data stored in entries of a first side or a second side of a cache of a branch predictor indicates that a branch is to be taken by either of the entries; the cache being segmented into the first side and the second side, where the entries on the first side correspond to a set of addresses having even-numbered indexes, and entries on the second side correspond to a set of addresses having odd-numbered indexes;
storing said branch predictions in a queue; and
~~delivering said bypassing a branch prediction to an instruction fetch unit during the same two clock cycle period as it by the end of a clock cycle in which said branch prediction is stored in said queue.~~
2. (Previously Presented) The method as in claim 1, wherein said prediction period comprises two clock cycles.
3. (Cancelled)
4. (Previously presented) The method as in claim 1, wherein an index of one of two sequential lines corresponds to an entry on said first side of said cache, and an index of another of said two sequential lines corresponds to an entry on said second side of said cache.
5. (Cancelled)
6. (Original) The method as in claim 1, comprising generating branch predictions for a stream of addresses during a stall of said instruction fetch unit.
7. (Original) The method as in claim 1, comprising generating during a cycle a prediction for a line, said line being other than the line being fetched by said instruction fetch unit during said cycle.
8. (Original) The method as in claim 1, wherein the addresses for which predictions are generated by a branch prediction unit are decoupled from the addresses for which lines are fetched by said instruction fetch unit.
9. (Cancelled)
10. (Cancelled)

APPLICANT(S): GAT, Tal et al.
SERIAL NO.: 10/748,173
FILED: December 31, 2003
Page 3

11. (Previously Presented) The method as in claim 1, comprising delivering a branch prediction to said instruction fetch unit in the same prediction period as said branch prediction is written to said queue.

12. (Currently Amended) A processor for generating branch predictions for two sequential lines in parallel during a prediction period, the processor comprising:

an instruction fetch unit; and

a branch prediction unit comprising a cache whose entries are segmented into a first side and a second side, where entries on the first side correspond to a set of addresses having even-numbered indexes, and entries on the second side correspond to a set of addresses having odd-numbered indexes; and

a queue to store branch predictions,

wherein said branch prediction unit is to bypass a branch prediction to said instruction fetch unit by the end of a clock cycle in which said branch prediction is stored in said queue, comprising a queue to store branch predictions, said branch prediction unit to generate branch predictions for two sequential lines in parallel during a prediction period, and said branch prediction unit to deliver said branch predictions to said instruction fetch unit during the same two clock cycle period as it is stored in said queue, wherein the branch prediction unit comprises a cache whose entries are segmented into a first side and a second side, where entries on the first side correspond to a set of addresses having even-numbered indexes, and entries on the second side correspond to a set of addresses having odd-numbered indexes.

13. (Cancelled)

14. (Previously Presented) The processor as in claim 12, wherein said cache is to store odd-numbered addresses in a first segment of said cache, and even-numbered addresses in a second segment of said cache.

15. (Previously Presented) The processor as in claim 12, wherein said prediction period comprises two clock cycles.

16. (Original) The processor as in claim 12, wherein said branch prediction unit is, in a prediction period, to write a branch prediction to said queue and to deliver said branch prediction to said instruction fetch unit.

17. -19. (Cancelled)

APPLICANT(S): GAT, Tal et al.
SERIAL NO.: 10/748,173
FILED: December 31, 2003
Page 4

20. (Currently Amended) A system comprising:

a dynamic random access memory unit; and

a processor for generating branch predictions for two sequential lines in parallel during a prediction period, the processor comprising:

an instruction fetch unit; and

a branch prediction unit comprising a cache whose entries are segmented into a first side and a second side, where entries on the first side correspond to a set of addresses having even-numbered indexes, and entries on the second side correspond to a set of addresses having odd-numbered indexes; and

a queue to store branch predictions and to decouple said branch prediction unit from said instruction fetch unit.

wherein said branch prediction unit is to bypass a branch prediction to said instruction fetch unit by the end of a clock cycle in which said branch prediction is stored in said queue. ~~comprising a queue to store branch predictions, said branch prediction unit to generate branch predictions for two sequential lines in parallel during a prediction period, and said branch prediction unit to deliver said branch predictions to said instruction fetch unit during the same two clock cycle period as it is stored in said queue, wherein the branch prediction unit comprises a cache whose entries are segmented into a first side and a second side, where entries on the first side correspond to a set of addresses having even-numbered indexes, and entries on the second side correspond to a set of addresses having odd-numbered indexes.~~

21. (Cancelled)

22. (Previously Presented) A system as in claim 20, wherein said cache is configured to store odd addresses in said odd side, and even addresses in said even side.

23. (Previously Presented) The system as in claim 20, wherein said prediction period comprises two clock cycles.

24. (Previously Presented) The system as in claim 20, wherein said branch prediction unit is, in a prediction period, to write a branch prediction to said queue and to deliver said branch prediction to said instruction fetch unit.

APPLICANT(S): GAT, Tal et al.
SERIAL NO.: 10/748,173
FILED: December 31, 2003
Page 5

25. (Previously Presented) The system as in claim 20, wherein the addresses for which predictions are generated by said branch prediction unit are decoupled from the addresses for which lines are fetched by said instruction fetch unit.